

### In the Claims

Please cancel claims 5, 10, 13 and 30 without prejudice. Applicants reserve the right to pursue the original subject matter in a continuing application. Please amend claims 1-4, 6-9, 11-12, 20-21, 24, 26-29, and 31-32; and add claims 33-34 as follows.

1. **(Currently Amended)** A privacy enclosure, comprising:
  - a) a rigid enclosure structure including a first wall structure and a second wall structure, the rigid enclosure structure having a stowed configuration and an expanded configuration, the rigid enclosure structure being configured to:
    - i) lift from the stowed configuration to provide expansion in a first vertical direction; and
    - ii) extend laterally to provide expansion in a second lateral direction, wherein at least one of the first and second wall structures is configured to slide relative to the other in the second lateral direction;
  - b) wherein the expanded configuration of the rigid enclosure structure is being defined by expansion of the rigid enclosure structure in the first vertical direction and the second lateral direction; and
  - c) wherein the rigid enclosure structure includes an upper region and a lower region, the upper region of the rigid enclosure structure being configured to stow within the lower region.
2. **(Currently Amended)** The privacy enclosure of claim 1, wherein the first wall structure of the rigid enclosure structure includes a pivoting wall structure having ~~has~~ a first end and a second end, the first end being configured to pivot upward relative to the second end to provide expansion in the first vertical direction.
3. **(Currently Amended)** The privacy enclosure of claim 2, wherein the second wall structure of the rigid enclosure structure includes a sidewall construction ~~is~~ joined to

the ~~pivoting~~ first wall structure, the ~~sidewall construction~~ second wall structure being configured to extend laterally outward from the ~~pivoting~~ first wall structure.

4. **(Currently Amended)** The privacy enclosure of claim 3, wherein the ~~sidewall construction~~ second wall structure includes a first sidewall construction fixed to the ~~pivoting~~ first wall structure and a second moveable sidewall construction, the second moveable sidewall construction being configured to move relative to the first sidewall construction.

5. **(Cancelled)**

6. **(Currently Amended)** The privacy enclosure of claim 1 ~~5~~, further including a base that defines the lower region of the rigid enclosure structure, the upper region of the rigid enclosure structure being sized to fit within the base when the rigid enclosure structure is in the stowed configuration.

7. **(Currently Amended)** The privacy enclosure of claim 6, wherein upper region of the rigid enclosure structure includes ~~a pivoting~~ the first wall structure, the first wall structure being configured to pivot to provide expansion in the first vertical direction, the ~~pivoting first wall structure~~ and the base defining a bench for seating when the rigid enclosure structure is in the stowed configuration.

8. **(Currently Amended)** The privacy enclosure of claim 1 ~~5~~, wherein the upper region includes a first door section and the lower region includes a second door section, the first and second door sections being configured to interlock with one another when the rigid enclosure structure is in the expanded configuration.

9. **(Currently Amended)** The privacy enclosure of claim 1 ~~5~~, wherein the upper region includes a necked portion and the lower region includes an opening, the necked portion of the upper region being configured to fit within the opening of the lower region

when the rigid enclosure structure is raised from the stowed configuration to provide expansion in the first vertical direction.

10. **(Cancelled)**

11. **(Currently Amended)** The privacy enclosure of claim 1-10, wherein the first and second wall ~~sections~~ structures include a tongue and groove arrangement to provide expansion in the second lateral direction.

12. **(Currently Amended)** A privacy enclosure, comprising:

- a) a plurality of rigid walls defining an interior, the interior being sized for use as a changing room, the rigid walls including at least a first rigid wall and a second rigid wall, wherein:
  - i) the first rigid wall is configured to pivot upward from a first position to a generally vertical position in relation to a floor, the first rigid wall including a seating area configured to seat users when the first rigid wall is positioned in the first position, the seating area being located a distance above the floor; and
  - ii) the second rigid wall is configured to laterally extend in a direction outward from the first rigid wall when the first rigid wall is in the vertical position.

13. **(Cancelled)**

14. **(Original)** The enclosure of claim 12, wherein the second rigid wall includes a first section fixed relative to the first rigid wall, and a second section slideable relative to the first section, the second section being configured to slide in the direction outward from the first rigid wall when the first rigid wall is in the vertical position.

15. **(Original)** The enclosure of claim 14, wherein the first and second sections of the second rigid wall are nested when the first rigid wall is positioned in the first position.

16. (Original) A privacy enclosure arrangement, comprising:

- a) a lower base;
- b) a stowable enclosure coupled to the lower base, the stowable enclosure including:
  - i) a rigid outer wall structure configured to expand from a stowed configuration to an expanded configuration;
- c) wherein at least a portion of the lower base and the rigid outer wall structure define an interior when the rigid outer wall structure is in the expanded configuration;
- d) a storage compartment located adjacent to the interior of the privacy enclosure arrangement; and
- e) a toilet moveable between the storage compartment and the interior of the privacy enclosure arrangement.

17. (Original) The arrangement of claim 16, wherein the toilet is arranged to selectively slide out from the storage compartment when the rigid outer wall structure is in the expanded configuration.

18. (Original) The arrangement of claim 16, wherein the storage compartment is defined by the lower base.

19. (Original) The arrangement of claim 16, wherein the rigid outer wall structure expands from the stowed configuration to the expanded configuration in a first direction and then a second direction perpendicular to the first direction.

20. **(Currently Amended)** A boat having a privacy enclosure, the privacy enclosure comprising:

- a) an enclosure structure having a rigid exterior, the rigid exterior including:
  - i) a plurality of wall structures; and
  - ii) a door hinged to one of the plurality of wall structures;

- b) the enclosure structure being selectively positionable in:
  - i) a collapsed configuration that permits the enclosure to be stowed; and
  - ii) an expanded configuration wherein an average-sized adult can stand within ~~the~~ an interior volume of the enclosure;
- c) the enclosure structure defining a toilet region and a changing room region when selectively positioned in the expanded configuration, the changing room region being adjacent to the toilet region; and
- d) a toilet positioned within the enclosure structure when the enclosure structure is in both the collapsed configuration and the expanded configuration.

21. **(Currently Amended)** The boat of claim 20, ~~further including a~~ wherein the toilet is moveable between the toilet region and a storage region of the enclosure structure.

22. (Original) The boat of claim 21, wherein the changing room region enlarges when the toilet is moved into the storage region.

23. (Original) The boat of claim 20, wherein the changing room region extends a length beyond the toilet region, the length being in the range of about 24 inches and 36 inches.

24. **(Currently Amended)** The boat of claim 20, wherein the changing room region extends at least [[\_\_\_\_]] 24 inches beyond the toilet region.

25. (Original) The boat of claim 20, wherein the enclosure structure is positionable in:

- a) a first position having a first height;
- b) a second position having an initial length and a second height, the second height being greater than the first height; and

- c) a third position having an extended length, the extended length being greater than the initial length.

26. **(Currently Amended)** The boat of claim 20, wherein the enclosure structure includes a base, the plurality of wall ~~structure~~ structures being selectively positionable ~~positioning~~ within the base.

27. **(Currently Amended)** The boat of claim 26, wherein the base includes a compartment sized and configured to stow ~~[[a]]~~ the toilet.

28. **(Currently Amended)** The boat of claim 20, wherein the enclosure structure is ~~secure-to~~ secured to a deck of the boat.

29. **(Currently Amended)** A method of expanding a privacy enclosure, the method comprising:

- a) providing an enclosure structure;
- b) raising the enclosure structure from a reduced height configuration to a raised height configuration by pivoting a first wall of the enclosure structure to a generally vertical orientation, the raised height configuration permitting an average-sized adult to stand within the enclosure structure; and
- c) laterally expanding the enclosure structure from a first length to a second increased length by sliding a second wall in a direction relative to the first wall.

30. **(Cancelled)**

31. **(Currently Amended)** The method of claim 29, wherein the step of ~~expanding the enclosure structure~~ sliding the second wall includes pulling ~~[[a]]~~ the second wall laterally outward from the first wall.

32. **(Currently Amended)** An privacy enclosure, comprising:
- a) ~~a rigid wall~~ an enclosure construction selectively positionable in a stowed configuration and an expanded configuration, the enclosure construction including a plurality of rigid walls;
  - b) a main interior defined by the plurality of rigid walls ~~wall construction~~;
  - c) a toilet storage region located adjacent to the main interior; and
  - d) a toilet movable between the main interior and the toilet storage region.
33. **(New)** A privacy enclosure arrangement, comprising:
- a) a lower base;
  - b) a stowable enclosure coupled to the lower base, the stowable enclosure including:
    - i) a rigid outer wall structure configured to expand from a stowed configuration to an expanded configuration, the rigid outer wall structure expanding from the stowed configuration to the expanded configuration in a first direction and then a second direction perpendicular to the first direction;
  - c) wherein at least a portion of the lower base and the rigid outer wall structure define an interior when the rigid outer wall structure is in the expanded configuration;
  - d) a storage compartment located adjacent to the interior of the privacy enclosure arrangement; and
  - e) a toilet moveable between the storage compartment and the interior of the privacy enclosure arrangement.
34. **(New)** A boat having a privacy enclosure, the privacy enclosure comprising:
- a) an enclosure structure having a rigid exterior, the rigid exterior including:
    - i) a plurality of wall structures; and
    - ii) a door hinged to one of the plurality of wall structures;
  - b) the enclosure structure being selectively positionable in:

- i) a first position having a first height, the first position defining a collapsed configuration that permits the enclosure to be stowed;
  - ii) a second position having an initial length and a second height, the second height being greater than the first height; and
  - ii) a third position having an extended length, in addition to the second height, the extended length being greater than the initial length, the third position defining an expanded configuration wherein an average-sized adult can stand within an interior volume of the enclosure;
- c) the enclosure structure defining a toilet region and a changing room region when selectively positioned in the expanded configuration, the changing room region being adjacent to the toilet region.